

# NH-2700T

## Through the Wall ATM

### Features

- **Maximum Reliability** - NH-2700T is designed to provide the utmost reliability in the retail market locations with maximum availability and with minimum maintenance needs.
- **Environment Stewardship** - With quality also comes responsibility. NH-2700T is equipped with energy saving features like low energy LCD and long lasting ATM parts with minimum implications to the environment.
- **Flexibility** - NH-2700T is designed with an open architecture platform allowing for easy future upgrades and module modifications. Modular design is one way to reduce total cost of ownership.
- **Ultimate Functionality** - NH-2700T offers a wide range of transactions utilizing a user-friendly interface, in a compact footprint. The integrated topper allows for advertising and branding.
- **Maximum Protection** - Complying with standards in various regions worldwide, Nautilus Hyosung offers advanced security measures while highly secured integrity of the NH-2700T prevents any attempted security breaches from occurring. NH-2700T can also be easily integrated with monitoring solutions to provide seamless data transfer for effective management of the self-service channels.



Driving tomorrow's technology  
**NAUTILUS HYOSUNG**



### Dependable Customer Service:

We understand the importance of speedy resolution to any issues arising in the operation. Our representatives offer real solutions with real results for maximum return on your investment.



# NH-2700T



## System Platform

- Microsoft® Window® CE platform

## Communication

- TCP/IP, Dial-up

## Display

- 10" wide TFT color LCD
- **Optional** rear Supervisor panel

## Input Type

- 4x2 Touch function keys
- **Optional** touch screen
- PCI compliant EPP  
T-DES, DES, RSA
- **Optional** RKT

## Security

- UL 291 Business hours safe
- Mechanical combination lock
- Electronic lock
- KABA Mas cencon lock

## Card reader

- Dip type card reader
- **Optional** IC card reader  
(EMV level 1,2 compliant)

## Cash dispenser

- 2,000 notes cassette (Up to 3)

## Printers

- Graphical thermal receipt printer

## Additional Features

- Lead-through indicator
- Audio jack
- Speaker
- Illuminated topper

## Wall Kit

- 3 in. throat (standard)
- **Optional** 10 in. throat

## Power Supply

- AC 110 ~ 240V, 50 ~ 60 Hz

## Environmental Conditions

- Temperature  
0°C ~ 40°C ( 32°F ~ 104°F )
- Humidity  
25% ~ 85%

## Dimensions

- Height : 72 in.
- Width : 21.50 in.
- Depth : 25.24 in.
- Weight : 308.64 lbs.

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Contact your authorized Nautilus Hyosung distributor or representative for more information.